

WDHT Series Downhole Tool

The WDHT Series of rupture disks were designed for pressure relief of oil tools to safely protect downhole components. There are many other applications that can benefit from this design, including wellhead protection, cementing, pressure activation equipment, spray washers, OEM's, laboratories, and more.

Features

- Each WDHT assembly consists of a threaded body with rupture disk welded onto the process side
- Body materials: 304 series Stainless Steel with other materials available on request
- Standard rupture disk material: Inconel (other materials available)
- Burst ratings 500 psig to 15,000 psig (for higher pressures contact ZOOK)
- 0% manufacturing range
- Operating ratios up to 75% of the low end of burst tolerance
- Requires Hex Key installation
- NPT threaded bodies
- Burst tolerance ± 10%
- Standard WDHTs in stock
- Customized designs available
- 100% factory leak-tested to bubble tight in liquid. For gas service or helium leak testing, please contact ZOOK
- 100% electronic thread verification of every assembly utilizing digital imaging
- 100% ultra-sonically cleaned prior to shipment
- 100% disk material traceability and burst test certification available
- CE (PED) compliance available

ZOOK's Welded Design Advantage

- Welded joints are stronger and more resistant to increased temperatures, which eliminates spurious bursts and product contamination
- Joint failure is eliminated due to increased temperature and pressure cycling compared to soldered joints
- Material creep is removed ensuring burst repeatability
- Improved quality and operational excellence





| WDHT Dimensions | | | | | | | |
|-----------------|---------------|---------------|--------------------------|-------------------------|-----------------------------|------------------------------------|---------------------------------|
| NPT Size | Min (psig) | Max (psig) | Hex Size " A " | Nom. 0D " B " | Thread Size " C " | Approximate Length " D " | Approximate Bore Size "E" |
| 1/8" | 1,000 | 15,000 | 3/16" | 0.405" | 1/8-27 NPT | 5/16" | 3/16" |
| 1/4" | 1,000 | 15,000 | 1/4" | 0.540" | 1/4-18 NPT | 7/16" | 3/16" |
| 3/8" | 1,000 | 15,000 | 5/16" | 0.675" | 3/8-18 NPT | 1/2" | 5/16" |
| 1/2" | 800 | 15,000 | 3/8" | 0.840" | 1/2-14 NPT | 9/16" | 3/8" |
| 3/4" | 500 | 7,350 | 9/16" | 1.050" | 3/4-14 NPT | 5/8" | 9/16" |
| 1" | 500 | 3,500 | 5/8" | 1.315" | 1-11-1/2 NPT | 3/4" | 5/8" |



zookdisk.com

SERVING AMERICA, CENTRAL & SOUTH AMERICA 16809 Park Circle Drive Chagrin Falls, Ohio 44022 United States Toll Free: +1 800 543 1043 Phone: +1 440 543 1010 E-mail: sales@zookdisk.com

SERVING EUROPE, MIDDLE EAST & AFRICA Navigation House, Bridge St.

Killamarsh, Sheffield, SŽ1 1AL United Kingdom Phone: +44 (0) 1909 560999 E-mail: sales.europe@zookdisk.com

SERVING CANADA

4400 South Service Road Burlington, Ontario, L7L 5R8 Canada Toll Free: +1 800 370 6057 Phone: +1 905 681 2885 E-mail: sales.canada@zookdisk.com

SERVING ASIA PACIFIC

Menara LGB TTDI Unit 6-3A, Level 6, Menara LGB, No. 1, Jalan Wan Kadir, Taman Tun Dr. Ismail, 60000 Kuala Lumpur, Malaysia Phone: +603 2706 0098 E-mail: sales.asia@zookdisk.com