

The ZANITARY® Series is an advanced sanitary disk designed for the biotechnology, pharmaceutical and food processing industries. The new design effortlessly fits between standard sanitary ferrules.



Features

- Ideal for high purity and corrosion resistant service that is required from the Life Science Industry
- Designed for non-fragmentation
- Solid metal robust design provides greater protection for low pressure rated disks
- Operating ratios up to 95% of the low end of burst tolerance (ZAN), and 100% of the low end of burst tolerance (ZAN95)
- Passivation finish to reduce the possibility of contamination
- Standard surface finish 4 - 20 Ra μin (0.1 - 0.5 Ra μm)
- Withstands full vacuum without the need of a separate vacuum support
- Suitable for liquid, gas, or two-phase applications
- Damage ratio of 1.0 or less*
- Expected cycle life of this new disk technology is 30,000 with full vacuum cycling and approximately 1,000,000+ without full vacuum
- Disks available in 316L and Hastelloy
- Suitable for use with NovAseptic flange mountings
- Unique design is Patent Pending
- No dents or crevices to the process side of the disk
- Ferrule design compliant and certified to 3-A Sanitary Standard
- Sizes from 1"(25mm) through 4"(100mm)
- Cleaned for Oxygen service available
- Nitrogen bagging available
- 3-dimensional stainless steel tag permanently laser engraved with disk information in accordance to ASME and PED
- No paint or enamel used on tagging to ensure non-contamination of the sterile environment
- Suitable for Clean-in-place (CIP) applications. Note: Disk dome should not be subject to contact or direct jet spray
- Electropolishing available meeting ASME BPE SF4
- CRN registered for use in Canada
- Complies ASME BPE Standard
- ASME UD, CE (PED), KOSHA and TÜV compliance available
 - Hastelloy – Trademark of Haynes International
 - NovAseptic – Trademark of Millipore Corporation

*Hastelloy and Liner equipped disks have a damage ratio of 1.5 or less

Models

- ZAN** Standard operating ratio up to 95% of the low end of burst tolerance
- ZAN95** Engineered operating ratio up to 100% of the low end of burst tolerance and includes plus testing as standard

Options

- ZAN+** Factory tested to 100% of the low end of the tolerance to ensure no disks will burst low
- ZAN-L*** A process side PFA Teflon liner provides extra protection from corrosion or viscous process build-up (PEEK liner required for 3A compliance)
- ZAN-BI*** Equipped with ZOOK's Integral Burst Indicator
- ZAN-EP** Electropolishing available in accordance to ASME BPE SF4

Note: *The maximum temperature rating of rupture disks supplied with liners and BI's is lower than the base disk material

Ferrule Standard and NovAseptic Flanges

The ZANITARY® can be installed into the Tri-Clover, BS, DIN, and ISO Standard ferrules along with the NA tank connectors as per the following:

- Tri-Clover
- ASME BPE
- BS4825-3 1991*
- ISO 2852-1993 (Second Edition 1993-06-15)*
- DIN 32676-2001-02*

*Contact ZOOK for more information

ZANITARY® Series Specifications

Minimum and Maximum Pressure Ratings - psig (barg) @ 72°F (22°C)

Disk Size	Minimum Burst Pressure (psig/barg)				Maximum Burst Pressure (psig/barg)	MNFA in ² (mm ²)	Tri-Clover Ferrule Dimensions in (mm)		
	316L	Hastelloy C276	ZAN-L*	ZAN-BI			Ferrule OD	Tube ID	
1"	35	65	85	+5 psig (+0.34 barg) of base material	300	0.43	1.98	0.87	
25 mm	2.414	4.482	5.861		20.684	277	50.4	22.1	
1-1/2"	15	25	45		250	1.08	1.98	1.37	
40 mm	1.035	1.724	3.103		17.236	696	50.4	34.8	
2"	11	25	35		180	2.05	2.52	1.87	
50 mm	0.759	1.724	2.414		12.410	1322	63.9	47.5	
2-1/2"	11	25	35		145	3.25	3.05	2.37	
64 mm	0.759	1.724	2.414		9.997	2096	77.4	60.2	
3"	11	20	30		120	4.71	3.58	2.87	
80 mm	0.759	1.379	2.069		8.273	3038	90.9	72.9	
4"	11	20	30		80	8.49	4.68	3.83	
100 mm	0.759	1.379	2.069		5.515	5477	118.9	97.4	
Max. Temp.	Dependant on the gasket material used								

Notes:

- * For PFA Liner, contact ZOOK for PEEK minimums
- For materials, sizes, burst ratings and temperatures not shown, contact ZOOK
- Contact ZOOK for higher temperatures

Manufacturing Design Range & Total Performance Tolerance

Models	ASME					PED			Operating* Ratio
	Burst Pressure (psig)		Manufacturing Design Range	Burst Tolerance	Operating Ratio*	Burst Pressure (barg)		Total Tolerance	
	Minimum	Maximum				Minimum	Maximum		
ZAN95	11.0	<15	0%	±1.3 psig	100%	0.690	<1.034	±0.090 barg	100%
ZAN, ZAN+	11.0	<15	0%	±1.3 psig	95%	0.690	<1.034	±0.090 barg	95%
ZAN95	15.0	<26	0%	±2.0 psig	100%	1.034	<1.793	±0.138 barg	100%
ZAN, ZAN+	15.0	<26	0%	±2.0 psig	95%	1.034	<1.793	±0.138 barg	95%
ZAN95	26.0	<40	0%	±2.0 psig	100%	1.793	<2.758	±0.138 barg	100%
ZAN, ZAN+	26.0	<40	0%	±2.0 psig	95%	1.793	<2.758	±0.138 barg	95%
ZAN95	40	Max	0%	±5 %	100%	2.758	Max	±5%	100%
ZAN, ZAN+	40	Max	0%	±5 %	95%	2.758	Max	±5%	95%

* Operating ratio from minimum of burst tolerance (total tolerance)

Notes:

- 0% manufacturing range might not be available in all materials
- Burst tolerances are the maximum expected variation from the disk's marked burst pressure

FDA Certified Gaskets (other materials on request)

Standard Gasket Materials (Stocked)			Temperature Range	
Materials	Cured	Colour	Min	Max
Viton	Bisphenol	Black	0° F (-18° C)	400° F (204° C)
Buna	Sulfur		-20° F (-29° C)	230° F (110° C)
EPDM	Peroxide		-67° F (-55° C)	347° F (175° C)
PTFE	-	White	-20° F (-29° C)	500° F (260° C)
Other Available Gasket Materials			Temperature Range	
Materials	Cured	Colour	Min	Max
Silicone	Peroxide	Red	-65° F (-54° C)	400° F (204° C)
		White		
		Black		
		Clear		
	Platinum	Clear	-76° F (-60° C)	400° F (204° C)
Viton	Bisphenol	White	0° F (-18° C)	400° F (204° C)
Buna	Sulfur		-20° F (-29° C)	230° F (110° C)
EPDM	Peroxide		-67° F (-55° C)	347° F (175° C)

Notes: A full copy of the Gaskets Certificate of Compliance can be accessed [here](#).

Certified Flow Resistance Factors

Disk Type	K _{r1} (liquid)	K _{rg} (Gas)
ZANITARY	4.08	4.08

Teflon - Trademark of The Chemours Company
 Tri-clamp/Tri-clover – Trademark of Alfa Laval
 Torque-Rite – Trademark of Rubber Fab

Zanitary_datasheet_052023

zookdisk.com



SERVING AMERICA, CENTRAL & SOUTH AMERICA

16809 Park Circle Drive
 Chagrin Falls, Ohio 44022
 United States
 Toll Free: +1 800 543 1043
 Phone: +1 440 543 1010
 E-mail: sales@zookdisk.com

SERVING EUROPE, MIDDLE EAST & AFRICA

Navigation House, Bridge St.
 Killamarsh, Sheffield, S21 1AL
 United Kingdom
 Phone: +44 (0) 1909 560999
 E-mail: sales.europe@zookdisk.com

SERVING CANADA

4400 South Service Road
 Burlington, Ontario, L7L 5R8
 Canada
 Toll Free: +1 800 370 6057
 Phone: +1 905 681 2885
 E-mail: sales.canada@zookdisk.com

SERVING ASIA PACIFIC

Menara LGB TTD1
 Unit 6-3A, Level 6, Menara LGB,
 No. 1, Jalan Wan Kadir,
 Taman Tun Dr. Ismail,
 60000 Kuala Lumpur, Malaysia
 Phone: +603 2706 0098
 E-mail: sales.asia@zookdisk.com

Safety through knowledge and performance.